

Linsn TS901 Sending Card

1.Function



- 1) One DVI video signal input;
- 2) Get signal from DVD player or media player, no intermediate device needed;
- 3) One Audio signal input;
- 4) Two network outputs; single port maximum support 655360 pixels;
- 5) Support adjusting brightness manually (require working with outer box); three scales can be set: 16-grade, 32-grade and 64-grade;

6) Support 60Hz and 30Hz output mode;

2. Capability

60Hz mode (using two ports)	30Hz mode (using two ports)
2048 × 640	4032 × 512
1920 × 672	3840 × 544
1792 × 720	3584 × 576
1600 × 800	3392 × 608
1472 × 880	3200 × 640
1344 × 960	3072 × 672
1280 × 1024	2880 × 704
1024 × 1280 (require supporting by graphics card)	2560 × 800
832 × 1280 (require supporting by graphics card)	2368 × 864
640 × 1280 (require supporting by graphics card)	2048 × 1024

2. Working conditions

Rated voltage (V)	5	maximum	5.5	minimum	4.5
Rated current (A)	0.50	maximum	0.57	minimum	0.46
Rated power consumption (W)	2.5	maximum	3.1	minimum	2.1
Working temperature (°C)	-20°C ~ 70°C				
Working humidity (%)	0% ~ 95%				







You can Get the [Linsn TS901 Sending Card](#) here